

## Trailer for foam drum and monitor

### Characteristics

- Trailer material : Carbon steel
- Typology : Single-axle trailer
- Drum positioning : Vertical
- Flanged connection for monitor
- Working deck
- Removable side supports for easy insertion and removal of drums
- Pneumatic tires
- Final coating: Polyurethanic red coat
- Foam casing suitable for foam 200 it foam drum.

### Executions on request

- Painting cycles on customer's request
- Hot dip galvanized trailer frame
- Triple way feeding
- Solid tyres

### Dimension

Height "H"	: 1.150 m (Monitor not included)
Width "L"	: 2.600 m
Depth "P"	: 1.450 m
Weight	: 230 kg (without drum)



Feeding  
Double way  
with internal clasp



## Trailer for monitors with steel foam tank

### Characteristics

- Trailer material : Carbon steel
- Cylinder material : Carbon steel or Stainless Steel
- Typology : Single-axle trailer
- Flanged connection for monitor.
- Front Working deck.
- Pneumatic tires
- Final coating : Polyurethanic red coat

### Executions on request

- Painting cycles on customer's request
- Hot dip galvanized trailer frame
- Triple way feeding
- Solid tyres

### Code

<b>82048_05</b>	500 it Steel cylinder
<b>82048_10</b>	1.000 it
<b>82048_15</b>	500 it Stainless steel cylinder
<b>82048_20</b>	1.000 it

Dimension	500	1.000
Height "H"	: 1.080 m	1.230 m
Width "L"	: 2.600 m	3.100 m
Depth "P"	: 1.550 m	1.550 m
Weight	: 450 kg	515 kg



Feeding  
Double way  
with internal clasp



## Mobile foam monitor

Made in according to custom specification , with foam stainless steel tank , mobile for high-risk areas.



Trolley with monitor 2 1/2" or 4" manifold with 4 inlets. Equipped with brakes, lights, foot stabilizers.



Trolley with tank 800 it complete with foam monitor, equipped with brakes, lights, foot stabilizers.



Trolley with tank 800 it manifold with 4 inlets, complete with foam monitor, equipped with brakes, lights, foot stabilizers.